


Your digital tool for the modern workplace

Boost your business growth and take your productivity to the next level with the ECOSYS PA3500cx printer. Made for medium to large-size work groups, this A4 color device is designed to stand the test of time with long-life components that help to reduce waste and ensure exceptional levels of reliability and data security.



Specifications

GENERAL

Configuration: Color Printer

Black/Color - Letter: 37 ppm; Legal: 30 ppm; A4: 35 ppm Duplex Print Speed: Letter 18.5 ppm; Legal 15 ppm; A4 17.5 ppm

Display: 5 Line LCD with 10 Key Control Panel Warm Up Time: 23 Seconds or Less (Power On) First Page Out Time:

Print: 5.7 Seconds or Less Black, 7.0 Seconds or Less Color Resolution: $1200 \times 1200 \text{ dpi}^{1}$, $9600 \text{ dpi} \times 600 \text{ dpi}$,

600 x 600 dpi

Memory: Std/Max: 1 GB / 1 GB

Duplex: Standard Stackless, Supports Statement to Legal $(5.5" \times 8.5" - 8.5" \times 14")$, 16 lb Bond - 90 lb Index (60 - 163gsm) Dimensions / Weight: 15.5" W x 20.9" D x 15.5" H 78.2 lb Maximum Monthly Duty Cycle: 100,000 Pages per Month

POWER CONSUMPTION

Electrical Requirements: 120V, 60Hz, 11.8A; 220-240V, 50/60Hz, 5.4A

Typical Electricity Consumption (TEC): 120V: 0.32 kWh/week; 220-240V 0.32 kWh/week

Maximum (Including options): 120V: 1,288W; 220-240V: 1,278W Printing: 120V: 541.6W; 220-240V: 496.4W Ready Mode: 120V: 11.1W; 220-240V: 11.8W Sleep Mode: 120V: 0.4W; 220-240V: 0.5W Power Off: 120V: 0.1 W; 220-240V: 0.1 W

PRINTER SPECIFICATIONS

Standard Controller: ARM Cortex-A9 Dual core 1.2GHz + ARM Cortex-M3 100MHz

PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL/PCL-5c), KPDL3, XPS, OpenXPS, PDF

Fonts: PCL6, KPDL, Calibri, Cambria and Bitmap

Barcodes: 1 Dimensional: 45 Type; 2 Dimensional: PDF417 1 Type

Windows OS Compatibility: Windows 8.1, Windows 10, Windows 11, Windows Server 2012/R2, 2016, 2019 MAC OS Compatability: MAC OS X 10.9 or greater

Google Chrome OS: version 118 or higher Linux OS Compatability: Linux PPD

Interfaces: 10 BASE-T/100 BASE-TX/1000 BASE-TX, 2 High-Speed USB 2.0 Ports, 1 Expansion Slot; Optional: Wireless IB-37, IB-38, IB-51

Mobile Printing: KYOCERA Mobile Print, KYOCERA MyPanel, KYOCERA Print Service Plugin, Apple AirPrint®, Mopria® Network Print and Supported Protocols: TCP/IP, IPv4, IPv6, NetBEUI, LPR, Port9100, IPP, WSD Print, DHCP, DNS, PNP-X, USB, LDAP/LDAPS, PDF Direct Print, PnP-X (WS-Discovery for WSD Print Service)

Drivers: KX Driver, PCL Uni Driver, KPDL Uni Driver, MAC Driver, Linux Driver, Chrome Driver Utilities: KYOCERA Net Direct Print, File Management Utility, KYOCERA Print Center, KYOCERA Net Viewer. KYOCERA Device Manager, ID Register, Web Installer, Quick Network Setup, Maintenance Menu, Kyocera Net Manager (Pro & Basic), ID Register, Wi-Fi Setup Tool, Command Center RX: KYOCERA Fleet Services (KFS) Additional Print Features: EcoPrint, Private Print, Proof and Hold, Quick Copy and Job Storage², Gloss Mode, Border Erase, Prevent Color Bleed-thru, Background Density

Adjustment; MPT: Banner Printing SECURITY SPECIFICATIONS

Standard: Local & Network Authentication, IPsec, HTTPS, SNMPv3, IPPS, POP over SSL; LDAPS, Overwrite & Data Encryption with optional SSD, SHA-2, TLS 1.3

PAPER SUPPLY

Standard Paper Sources: Single 550 Sheet Drawer, 100 Sheet Multipurpose Tray (20 lb. Bond) Standard / Maximum Paper Capacity: 650 Sheets / 2,300 Sheets

Paper Size: Statement to Legal (5.5" \times 8.5" - 8.5" \times 14"),

Custom; MPF: Envelope, Banner

Paper Weight: Standard / Optional Drawers: 16 lb. Bond - 32 lb. Bond. (60 - 120gsm); MPT: 16 lb. Bond - 110 lb. Index (60 - 220gsm) Standard Output Tray Capacity: 250 Sheets

Input Materials: Plain, Preprint, Bond, Recycled, Thin, Letterhead, Color, Pre-punched, Thick, High Quality, Custom; MPT; Envelope, Coated, Cardstock, Transparency, Labels

PAPER HANDLING OPTIONS

PF-5150: Paper Feed Cassette (550 Sheet x 3) Paper Size: Statement to Legal (5.5" x 8.5" – 8.5" x 14"), Envelope, Custom Paper Weight: 16 lb Bond – 120 lb Index (60 - 220 gsm)

Input Materials: Plain, Preprint, Bond, Recycled, Thin, Letterhead, Color, Pre-punched, Thick, High Quality, Custom; MPT; Envelope, Coated, Cardstock, Transparency, Labels Dimensions / Weight: 15.5" W x 21" D x 4.6" H / 9.7 lbs

ADDITIONAL OPTIONS

Print Management: ThinPrint (UG-33) Security: Optional: Card Authentication Kit (B)

SD Card: 16 /32 GB

SSD: HD-17: 64 GB SSD/ HD-18: 256 GB SSD/ HD-19: 512 GB SSD

Wireless LAN: IB-37, IB-38, IB-51

Additional NIC: IB-50 Dual Gigabit NIC

Barcode Flash Option for advanced barcode printing

Note:

¹At Reduced Speed

Requires Optional SD Card or SSD

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.







DS Business Life Simplified

New Jersey Office (HQ)

908 653 0600

New York Office 151 Sumner Avenue 505 8th Avenu Kenilworth, NJ 07033 New York, NY 10018

www.dsbls.com

212 468 5200

KYOCERA Document Solutions Partner

SEP2023ECOSYSPA3500cx/VER1.0

KYOCERA Document Solutions America 225 Sand Road, PO Box 40008 Fairfield, New Jersey 07004-0008, USA Tel: 973-808-8444



kyoceradocumentsolutions.us

^{*} KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.