



# Maximize your performance

The TASKalfa MA4500ci combines rapid print speeds with smooth device operation to empower users to print with optimized security and efficiency. Built with Kyocera's trademark long-life components, this device is assured to bring your business success today, tomorrow, and long into the future.



# **Specifications**

#### GENERAL

Configuration: Color MFP - Print / Scan / Copy / Fax Black/Color: Letter: 47 ppm; Legal: 38 ppm; A4: 45 ppm Duplex Print Speed: Letter 39 ppm; Legal 32 ppm; A4 37 ppm Display: 7" Color Touch Screen Control Panel (TSI) Warm Up Time: 26 Seconds or Less (Power On) First Page Out Time:

Copy: 5.7 Seconds or Less Black, 6.7 Seconds or Less Color Print: 5.1 Seconds or Less Black, 6.2 Seconds or Less Color **Resolution:** 1200 x 1200 dpi <sup>1</sup>, 9600 dpi x 600 dpi, 600 x 600 dpi Memory: Std/Max: 2 GB / 3 GB

**Duplex:** Standard Stackless, Supports Statement to Legal (5.5" x 8.5" - 8.5" x 14"), 16 lb Bond - 90 lb Index (60 - 163gsm) Dimensions / Weight: 18.9" W x 22.7" D x 23.6" H / 110 lb Maximum Monthly Duty Cycle: 100,000 Pages per Month

## **POWER CONSUMPTION**

Electrical Requirements: 120V, 60Hz, 9.9A; 220-240V, 50/60Hz, 5.4A **Typical Electricity Consumption (TEC):** 120V: 0.46 Wh/week; 220-240V 0.45 Wh/week Maximum (Including options): 120V: 1,360 W; 220-240V: 1,349 W Copy / Printing: 120V: 672.1W/668.1W; 220-240V: 610.1W/604.1 W Ready Mode: 120V: 18.4W; 220-240V: 18.8W

Sleep Mode: 120V: 0.5 W; 220-240V: 0.6 W Power Off: 120V: 0.1 W; 220-240V: 0.1 W

## PRINTER SPECIFICATIONS

Standard Controller: ARM Cortex-A9 Dual core 1.2GHz + ARM Cortex-M3 100MHz

PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL PCL-5c), KPDL3, XPS, OpenXPS, KPDL-PDF

Fonts: PCL, KPDL, Cambria, Calibri and Bitmap

Barcodes: 1 Dimensional: 45 Type; 2 Dimensional: PDF417 1 Type

Windows OS Compatibility: Windows 8.1, Windows 10, Windows 11, Windows Server 2012/R2, 2016, 2019

MAC OS Compatability: MAC OS X 10.9 or greater Google Chrome OS: version 118 or higher

Linux OS Compatability: Linux PPD Interfaces: 10 BASE-T/100 BASE-TX/1000 BASE-TX.

2 High-Speed USB 2.0 Ports, 1 Expansion Slot Optional: Wireless LAN IB-37, IB-38, IB-51

Mobile Printing: KYOCERA Mobile Print, KYOCERA MyPanel, KYOCERA Print Service Plugin, WIAScan,

ChromeOS(Scan), Apple AirPrint®, Mopria Network Print and Supported Protocols: TCP/IP, IPv4, IPv6, NetBEUI, FTP, LPR, Port9100, IPP, WSD Scan/Print, DHCP, DNS, PNP-X, USB, LDAP, SNMP, SMTP, PDF Direct Print, PnP-X (WS-Discovery for WSD Print Service) Drivers: KX Driver, PCL Uni Driver, KPDL Uni Driver,

Network FAX Driver, TWAIN Driver, WIA Network, WIA USB, TWAIN Box, MAC Driver, Linux Driver, Chrome Driver

Utilities: KYOCERA Net Direct Print, File Management Utility, KYOCERA Print Center, KYOCERA Net Viewer, KYOCERA Device Manager, ID Register, Scan to Folder Setup Tool for SMB, Web Installer, Quick Network Setup, Maintenance Menu, Kyocera Net Manager (Pro & Basic), ID Register, Wi-Fi Setup Tool, Command Center RX; KYOCERA Fleet Services (KFS) Additional Print Features: HyPAS capable<sup>2</sup>, EcoPrint, Private Print, Proof and Hold, Quick Copy and Job Storage<sup>2</sup>, Gloss Mode, Border Erase, Prevent Color Bleed-thru, Background Density Adjustment; MPT: Banner Printing

Standard: Local & Network Authentication, IPsec, HTTPS, SNMPv3, IPPS, POP over SSL, FTPS and LDAPS, SMTP over SSL, Overwrite & Data Encryption with optional SSD, SHA-2, TLS 1.3

### SCAN FUNCTIONS

Scan Type: Color and Black & White Scanner Scan Resolution: 300 dpi x 300 dpi, 200 dpi x 200 dpi (Default), 200 dpi x 100 dpi, 600 dpi x 600 dpi, 400 dpi x 400 dpi, 200 dpi x 400 dpi

Scanning Functions: PC (SMB), email (SMTP), USB, FTP, WSD, TWAIN/WIA; Continuous Scan, Mixed Originals, Blank Page Skip, ID Card Copy, DP Auto Crop File Formats: TIFF (MMR/JPEG compression), JPEG, PDF (MMR/JPEG compression), XPS, PDF/A-1,PDF/A-2, PDF (High compression), Encrypted PDF, OPEN XPS, Optional: MS Office & Searchable PDF with Scan Extension Kit (A) Scan Speeds: Simplex BW/Color: @300 dpi - 60ipm/50ipm;

@600 dpi - 40ipm/20ipm Duplex (DSDP) BW/Color: @300 dpi: 120ipm/100ipm:

@600 dpi 80ipm/40ipm **Original Size:** Min/Max: Glass/DP: Statement to Legal (5.5" x 8.5" - 8.5" x 14"); Banner: DP Up to 48"

## **COPY SPECIFICATIONS**

Image Mode: Text, Photo, Text & Photo, Graphic/Map, Printer Output

Copy Quantity: 1- 999 / Auto Reset to 1 Job Management: 200 Address Book Records, 100 Department Codes, 100 One-Touch Keys, 20 Program Keys, 6 Shortcut Keys Magnification / Zoom: Auto Zoom, Full Size, 7 Reduction, 5 Enlargement Preset Ratios, 25% - 400% in 1% Step Increments Additional Copy Features: Auto Paper Select (APS), Color Balance, Auto Color Select (ACS), Background Density Adjustment, Auto Zoom, Auto Duplex, Continuous Scan, Blank Page Skip, ID Card Copy, Quiet Mode

# DOCUMENT PROCESSOR

(50 – 120gsm)

Type / Capacity: Dual Scan Document Processor (DSDP) / 100 Sheets Acceptable Originals: Statement to Legal (5.5" x 8.5" — Acceptable Weights: Simplex / Duplex: 13 - 32 lb Bond

### FAX SPECIFICATIONS

Compatibility / Data Compression: ITU-T G3 Fax / MMR, MR, MH, JBIG Transmission Speed / Modem Speed: 33.6kbps Fax Memory: 3.5 MB

Fax Functions: Forwarding, Polling TX/RX, Multiport Destination, Network Fax TX/RX, Duplex TX/RX, Density adjustment, Original Image Quality, Original Type 1-Sided/2-Sided, Send Size, Continuous scan, Direct Transmission, Mixed Originals (Same Width), Banner

Standard Paper Sources: Single 550 Sheet Drawer,

# PAPER SUPPLY

100 Sheet Multipurpose Tray (20 lb. Bond ) Standard / Maximum Paper Source 2 / 6 Including Multipurpose Tray Standard / Maximum Paper Capacity: 650 Sheets / 2,850 Sheets Paper Output Capacity: 250 Sheets Paper Size: Standard and MPT: Statement to Legal (5.5" x 8.5" - 8.5" x 14"), Custom Paper Weight: Standard / Optional Drawers: 16 lb. Bond - 32 lb. Bond. (60 - 120gsm); MPT: 16 lb. Bond - 110 lb. Index (60 - 220gsm) Input Materials: Plain, Preprint, Bond, Recycled, Thin, Letterhead, Color, Pre-punched, Thick, High Quality, Custom; MPT; Envelope, Coated, Cardstock, Transparency, Labels

**PAPER HANDLING OPTIONS PF-5150:** Paper Feed Cassette (550 Sheet x 4) Paper Size: Statement to Legal (5.5"  $\times$  8.5" - 8.5"  $\times$  14") MPT: Envelope, Custom

Paper Weight: 16 lb Bond – 120 lb Index (60 – 220gsm) Input Materials: Plain Paper, Bond Paper, Recycled Paper, Prepunched, Letterhead; MPT: Thick, Coated, Envelope Dimensions / Weight: 15.5" W x 21" D x 4.6" H / 9.7 lbs

ADDITIONAL OPTIONS
Print Management: ThinPrint (UG-33)
Security: Optional: Card Authentication Kit (B) **SD Card:** 16 /32 GB **SSD:** HD-17: 64 GB SSD / HD-18: 256 GB SSD/ HD-19: 512 GB SSD Wireless LAN: IB-37, IB-38, and IB-51 which does not support HyPAS or KFS Additional NIC: IB-50 Dual Gigabit NIC Optional Memory: 1 GB DIMM Memory (DDR3) Other: Scan Extension Kit (A), USB Keyboard (Customer Supplied)

# Note:

<sup>1</sup>At Reduced Speed Requires Optional SD Card or SSD

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.









KYOCERA Document Solutions America 225 Sand Road, PO Box 40008 Fairfield, New Jersey 07004-0008, USA Tel: 973-808-8444

**Document Solutions** 151 Sumner Avenue, Kenilworth, New Jersey 07033

NY | NJ | PA

NJ: 908.653.0600 NY: 212.468.5200



service@dsbls.com www.dsbls.com

KYOCERA Document Solutions Partner

SFP2023MA4500ci/VFR1.0



kyoceradocumentsolutions.us