



1 14

EvolutionNext

TASKalfa MZ7001ci Series & MZ7001i Series

- + A3 color copy, print, scan, and optional fax in 1 device
- + Cloud connectivity out of the box
- + Up to 70 ppm and up to 274 ipm
- + True 1200 x 1200 dpi with advanced finishing

The TASKalfa MZ7001ci Series is our follow up to the Evolution Series - EvolutionNext. This product series includes 6 Color multifunction printers and 4 Black and White multifunction printers from 25 to 70 ppm. This series offers built-in cloud connectivity, industry-leading reliability, and AI capabilities in a sustainable design.



Pre-installed cloud applications simplify document capture, release, and management, saving time and resources.

Award-winning reliability

Durable components last up to three times longer than competing models. BLI named Kyocera the 2024-2026 Most Color Consistent A3 Brand and the 2025-2027 Most Reliable A3 Brand.



Taking productivity further

Al-powered features eliminate errors while industryleading dual scan processors streamline high-volume scanning.

C

Security by design

FIPS 140-3 compliance and advanced authentication provide the highest level of security.



Cost-efficient sustainability

Our toner lock technology reduces the need for service calls and minimizes waste.

Color or B&W	Brand/Family TASKalfa	Product Type M = MFP	Product Format Z = A3	Print Speed 25-70ppm	Version	Functionalities/ Identifier (c) Color (i) HyPAS enabled
Color	TASKalfa	м	Z	25/35/40/50/60/70	01	ci
B&W	TASKalfa	м	Z	40/50/60/70	01	i

Product Configuration: TASKalfa MZ7001ci Series at a Glance





Internal Punch Unit + PH-7100 - 2 and 3 hole punch capabilities for paper sizes between 5.5" x 8.5" - 12" x 18"



- **External Punch Unit** + PH-7A – 2 and 3 hole punch capabilities for paper sizes between 5.5" x 8.5" - 12" x 18"
- **Device Accessories** + DT-730B hard copy holder + Banner Guide 10 for easier banner paper feeding + Keyboard Holder 10 for optional keyboard **Memory Accessories** + HD-16 HDD (1TB)
- **Connectivity Accessories** + Fax system 12 for fax capabilities
 - + Internet Fax Kit (A) for internet fax capabilities + UG-33/34 for optimal
 - printer emulation

Software Accessories

- + Card Authentication Kit (B) for more secure printing
- + Scan Extension Kit (A), an extended option for OCR scanning



Fiery Print Controller

- + Fiery[®] Printing System 17
- + Interface Kit 15 (B)

Configure your TASKalfa device!

For more details on how to configure your device to match the needs of your office, navigate to our product configurator. The tool aims to pair you to the device configuration* that fits your specific business needs.

Scan or click the QR codes on this page to discover the solutions for you.



Integration with Kyocera solutions

Features		ксс	КСІМ	KCPS	DMConnect	PinPoint Scan
Document Capture	Capture, classify, process, and route documents to on-prem/cloud storage, DMS, ECM, and ECM	•			•	•
Connect to Cloud Storage	Not only send scanned documents but process them before sending to cloud storage	•		•		
Document Management	A DMS includes features such as version control, document indexing, search, and secure access control to enhance security and productivity.		•			
Print Management	Streamline and optimize printing activities by managing print jobs, controlling costs, tracking output, and enhancing security.			•		



*Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

MAIN UNIT

Type: B&W Laser MFP (40-70ppm); Color Laser MFP (25-70ppm) Functions: Standard: Print, Copy, Scan; **Optional:** Fax Control Panel: 10.1" Color Touch Screen Memory: 4 GB RAM Solid State Drive/Hard Disk Drive: Standard: 256 GB SSD; Optional: 1 TB HDD Interface Connection: Network: 1000Base-T/100Base-Tx/10BASE-T (IPv6, IPv4, IPSec), IEEE 802.3az; Other Standard: USB 2.0 (Hi-Speed USB), USB 3.0 (Super-Speed USB) Paper Capacity: Standard: 1,150 Sheets; Maximum: 7,150 Sheets Paper Sources: Standard: (2) 500 Sheet Paper Trays & (1) 150 Sheet Multi-Purpose Tray; Optional: (2) 500 Sheet Paper Trays, (1) Dual 1,500 Sheet Paper Trays, Cabinet Stand, and 3,000 Sheet Large Capacity Side Tray Finishing Capabilities: Internal Options: Stack,

Staple, 2 and 3 Hole Punch, Job Separator, Inner Shift Tray

External Options: 1,000 Sheets (50-Sheet Staple), 4,000 Sheets (65-Sheet Staple & 100-Sheet Staple), 2 and 3 Hole Punch, Booklet and Tri-Fold Units, 7-Bin Mailbox, Z-Fold Unit, Inserter Unit

NOTE: 4,000 Sheet External Finisher (100-Sheet Staple) only available on 40-70ppm MFPs, Z-Fold Unit and Inserter Unit only available on 60-70ppm MFPs

Supported Media Types:

Cassette: Plain, Vellum, Recycle, Preprint, Bond, Hagaki, Color, Punched, Letterhead, Thick, Envelope, High Quality, Custom Multi-Purpose Tray: Plain, Transparency (OHP film), Vellum, Labels, Recycle, Preprint, Bond, Hagaki, Color, Punched, Letterhead, Thick, Envelope, Coated, High Quality, Index Tab Dividers, Custom

Supported Media Sizes:

Cassette 1: 5.5" x 8.5" - 8.5" x 14" (statement to legal) Cassette 2: 5.5" x 8.5" - 12" x 18", **Custom Size**

Multi-Purpose Tray: 5.5" x 8.5" - 12" x 18" (multiple); to 12" x 48" Banner (single) Paper Weight: Cassette 1, Cassette 2, and Multi-Purpose Tray: 14 lb. Bond - 166 lb. Index (52 - 300 gsm)

Print Speed (B&W and Color): MZ2501ci: Up to 25ppm Letter, 15ppm Legal, and 12ppm Ledger MZ3501ci: Up to 35ppm Letter, 21ppm Legal, and 17ppm Ledger MZ4001ci: Up to 40ppm Letter, 24ppm Legal, and 20ppm Ledger MZ5001ci: Up to 50ppm Letter, 30ppm Legal, and 25ppm Ledger MZ6001ci: Up to 60ppm Letter, 36ppm Legal, and 30ppm Ledger MZ7001ci: Up to 70ppm Letter, 42ppm Legal, and 35ppm Ledger Print Speed (B&W) MZ4001i: Up to 40ppm Letter, 24ppm Legal, and 20ppm Ledger MZ5001i: Up to 50ppm Letter, 30ppm Legal, and 25ppm Ledger MZ6001i: Up to 60ppm Letter, 36ppm Legal, and 30ppm Ledger MZ7001i: Up to 70ppm Letter, 42ppm Legal, and 35ppm Ledger Warm Up Time: MZ2501ci & MZ3501ci: 9.7 sec or less MZ4001i, MZ5001i, MZ6001i, & MZ7001i: 14.4 sec or less MZ4001ci, MZ5001ci, MZ6001ci: 14.4 sec or less MZ7001ci: 25 sec or less Dimensions (W x D x H): Approximately 23.7" × 26.1" × 31.1" (602mm × 663mm × 790mm) for all models Weight: MZ4001i, MZ5001i, MZ6001i, & MZ7001i: Approximately 182 lbs. (83 kg) MZ2501ci & MZ3501ci: Approximately 198.4 lbs. (90 kg) MZ4001ci, MZ5001ci, MZ6001ci, MZ7001ci: Approximately 209.4 lbs. (95 kg)

PRINT SPECIFICATIONS

Print Resolution: True: 1200 dpi x 1200 dpi; Enhanced: Up to 4800 dpi x 1200 dpi PDLs/Emulations: PCL6 (PCL XL/PCL 5c) for TASKalfa MZ2501ci, 3501ci, 4001ci, 5001ci, 6001ci, & 7001ci; PCL6 (PCL XL/PCL 5e) for TASKalfa MZ4001i, 5001i, 6001i, & 7001i; PRESCRIBE, KPDL3 (PostScript3 compatible) AES Support, PDF, XPS/OpenXPS, PPML, **Microsoft WPP and Universal Print**

Mobile Devices & Cloud Ready Printing:

Apple AirPrint®, Mopria®, Kyocera Cloud Print and Scan (KCPS), KYOCERA Mobile Print, & **KYOCERA** MyPanel

Fonts: 93 Fonts (PCL6), 136 Fonts (KPDL3), 4 Fonts (Calibri), 4 Fonts (Cambria), 1 Font Bitmap font, 79 Outline fonts

Operating Systems: Windows: 10/11; Server 2016/Server 2019/Server 2022/Server 2025; Mac OS X v10.0 or later; Chrome OS

COPY SPECIFICATIONS

First Copy Out Time: MZ2501ci: 6.4 seconds or less (B&W), 8.5 seconds or less (Color) MZ3501ci: 5.3 seconds or less (B&W), 7.0 seconds or less (Color) MZ4001ci: 4.5 seconds or less (B&W), 5.9 seconds or less (Color) MZ5001ci: 3.7 seconds or less (B&W), 4.8 seconds or less (Color) MZ6001ci & MZ7001ci: 3.4 seconds or less (B&W), 4.4 seconds or less (Color) MZ4001i: 4.5 seconds or less MZ5001i: 3.7 seconds or less MZ6001i & MZ7001i: 3.4 seconds or less Copy Resolution: 600 dpi x 600 dpi Continuous Copy: Up to 9,999 Sheets **Magnification (Manual Mode):** 25% to 400%. 1% increments Auto Mode Enlargements: 25%, 50%, 70%,

81%, 86%, 100%, 115%, 122%, 141%, 200%, 400%



SCAN SPECIFICATIONS

Types:

(2) Reverse Automatic Document Processors -DP-7140 & DP-7150

(2) Dual Scan Document Processors - DP-7160 & DP-7170

Document Processor Paper Capacity: DP-7140: 50 Sheets; DP-7150: 140 Sheets; DP-7160 & DP-7170: 320 Sheets

Document Processor Supported Media Sizes: DP-7140: Min: A5-R/Statement-R 5.5" x 8.5" (140 × 182mm), Max: A3/Ledger 11"x 17" (297 × 432mm), Banner: (297 × 1,600mm) DP-7150: Min: A6-R/Statement-R 5.5" x 8.5" (105 × 148mm), Max: A3/Ledger 11" x 17" (297 × 432mm), Banner: (297 × 1,600mm) DP-7160 & DP-7170: Min: A6-R/Statement-R 5.5" x 8.5" (105 × 148mm), Max: A3/Ledger 11" x 17" (297 × 432mm), Banner: (297 × 1,600mm) Document Processor Supported Media

Weights:

DP-7140 & DP-7150: Simplex: 13 lb. Bond – 90 lb. Index (35 to 160 gsm), Duplex: 16 lb. – 32 lb. Bond (50 to 120 gsm)

DP-7160 & DP-7170: Simplex: 13 lb. Bond – 120 lb. Index (35 to 220 gsm), Duplex: 16 lb. – 120 lb. Index (50 to 220 gsm)

Document Processor Speed:

DP-7140: Simplex: 50 ipm; Duplex: 16 ipm (B&W/Color)

DP-7150: Simplex: 80 ipm; Duplex: 48 ipm (B&W/Color)

DP-7160 & DP-7170: Simplex: 137 ipm; Duplex: 274 ipm (B&W/Color)

Cloud Ready Services: Kyocera Cloud Capture (KCC), Kyocera Cloud Information Manager (KCIM), Kyocera Cloud Print and Scan (KCPS) Resolution: Platen Glass: 600 dpi x 600 dpi, Document Processor: 600 dpi x 600 dpi / 600 dpi x 300 dpi

File Format: TIFF, JPEG, XPS, OpenXPS, PDF, Searchable PDF, MS Office File

OPTIONAL FAX SPECIFICATIONS

Modem Speed: G3: 33.6kbps

Compression Method: MMR,MR,MH,JBIG Resolution: 600 dpi x 600dpi, 400 dpi x 400 dpi, 200 dpi x 400 dpi, 200 dpi x 200 dpi, 200 dpi x 100 dpi

Sending/Recording Size:

Statement-R to 11" x 17"

Number of Transmission Lines: 1 standard line, up to 2 lines

Transmission Time: < 3 seconds when using JBIG

Fax Server Transmission Method: SMTP/ POP3 Via Server/SMTP Direct Communication (DirectSMTP)

Driver: Network Fax Driver

Memory Backup: Network Fax, Duplex Transmission and Reception, Encrypted Transmission and Reception, Polling Transmission and Reception, Broadcast, Fax Server Integration, Fax Dedicated Paper Feed Tray, Fax Forwarding to email or file

SECURITY SPECIFICATIONS

Guarded Access: LDAP, IP Filtering, Secure Print Release, SMTP Authentication, Create Encrypted PDF, Failed Authentication Lockout, Card Authentication

Protected Data Storage: SSD/HDD Overwrite, AES 256 Data Storage Encryption, Trusted Platform Module, IEC-15408, Common Criteria, IEEE 2600 Certified, HCD-PP Certified Secure Communication: TLS v1.3, SMB 3.1.1, HTTPS, ECDSA, FIPS 140-3 Encryption, S/ MIME, IPSec with HCD-PP, IPPS Printing (Over TLS), SCEP Certificated Enrollment, OCSP/CRL Certificates, 802.1X Ethernet Certificates, SHA 2 384

Advanced Management: 3 Preset Security Level Configurations, Remote Management of Fleet, SNMP v3 Monitoring, SIEM/Syslog Monitoring, Secure Boot Check, Run Time Integrity Checks, Allow List

ENVIRONMENTAL SPECIFICATIONS

Operating Environment: Temperature: 50 F - 90.5 F (10 - 32.5°C); Humidity: 10 - 80% RH (Relative Humidity)

Power Requirements: MZ7001ci: 120V, 60Hz, 16A, 2400W; 220-240V, 50/60Hz, 10A, 2400 W **Power Consumption:** All other models: 120V, 60Hz, 12A, 1650W; 220-240V, 50/60Hz, 7.2A, 1750W

Sleep Mode: Color MFPs: 0.5W, B&W MFPs: 0.4W

Typical Electricity Consumption (TEC) Rating:

MZ2501ci: 0.29 kWH (120V); 0.30 kWH (220-240V) MZ3501ci: 0.46 kWH (120V); 0.43 kWH (220-240V) MZ4001ci: 0.52 kWH (120V); 0.50 kWH (220-240V) MZ5001ci: 0.66 kWH (120V); 0.63 kWH (220-240V) MZ6001ci: 0.83 kWH (120V); 0.79 kWH (220-240V) MZ7001ci: 1.05 kWH (120V); 1.01 kWH (220-240V) MZ4001i: 0.49 kWH (120V); 0.47 kWH (220-240V) MZ5001i: 0.63kWH (120V); 0.60 kWH (220-240V) MZ6001i: 0.80 kWH (120V); 0.77 kWH (220-240V) MZ7001i: 0.98 kWH (120V); 0.93 kWH (220-240V) Standards: Energy Star and EPEAT

CONSUMABLES

Toner:

<u>MZ2501ci & MZ3501ci:</u> TK-8467C/M/Y/K <u>MZ4001ci, MZ5001ci, MZ6001ci, MZ7001ci:</u> TK-8597C/M/Y/K <u>MZ4001i, MZ5001i, MZ6001i, MZ7001i:</u> TK-6357K **Toner Yield (Estimated at 5% Coverage):** TK-8467C/M/Y/K: 20,000 Pages; TK-8467K: 30,000 Pages TK-8597C/M/Y/K: 24,000 Pages; TK-8597K: 40,000 Pages TK-6357K: 40,000 Pages

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. ECOSYS, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners. Kyocera Document Solutions has championed innovative technology since 1934. We enable our customers to turn information into knowledge, excel at learning and surpass others. With professional expertise and a culture of empathetic partnership, we help organizations put knowledge to work to drive change.

KYOCERA Document Solutions America 225 Sand Road, PO Box 40008 Fairfield, New Jersey 07004-0008, USA Tel: 973-808-8444





New Jersey Office (HQ) 151 Sumner Avenue Kenilworth, NJ 07033 908.653.0600 New York Office 505 8th Avenue New York, NY 10018 212.468.5200

www.dsbls.com

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ©2025 KYOCERA Document Solutions America, Inc.