

# 3i-R

## OFFICE WATER FILL STATION

Our Flagship Model



### HIGH CAPACITY

Large reservoir and compressor delivers constant cold water, even for large offices.



### STATE-OF-THE-ART PURIFICATION TECHNOLOGY

On-board, multi-stage, reverse osmosis purification.



### OPTIMAL DISPENSE HEIGHT & AREA

Ergonomic design for “no-bend” dispensing. Spacious dispense area for larger refillable bottles.



### CLEANCONTACT™ ANTI-MICROBIAL TOUCHPAD

Organic anti-microbial coating helps maintain the cleanliness of touch-pad.



### 24/7 SYSTEM MONITORING

Diagnostic center ensures system performance and water quality.



### DISPENSE AREA LIGHT

Enables precise dispensing and reduced likelihood of spillage.



### DENT-RESISTANT

Strong steel frame resists dents and damage.



### INDUSTRY-LEADING CERTIFICATIONS

Including EnergyStar, UL, ISO 9001/14001, and is certified by WQA according to NSF/ANSI 42, 58, and 372.



### TOUCHLESS-DISPENSE\*

Foot pedal activated design allows simple hands-free dispensing of hot and/or cold water.

\*Optional Feature



**DS Business Life Simplified**  
WATER TEAM

New Jersey Office (HQ)  
151 Sumner Avenue  
Kenilworth, NJ 07033  
908.653.0600  
www.dsbls.com

New York Office  
505 8th Avenue  
New York, NY 10018  
212.468.5200



PHSI manufactures water purification equipment in a state-of-the-art facility. Our systems are tested and certified to the highest standards for safety and performance, including EnergyStar, UL, ISO 9001/14001, and is certified by WQA according to NSF/ANSI 42, 58, and 372.

# 3i-R

## OFFICE WATER FILL STATION

Our Flagship Series

High-Capacity Chilling System

24/7 System Monitoring

CleanContact™  
Anti-Microbial Surfaces

Hot Water Safety Lock

Precision Dispense Light

High Capacity Drip Tray

On-Board Multi-Stage  
Purification System

Dent-Resistant  
Steel Frame

\*Optional Single & Dual Foot Pedal  
For TOUCHLESS Use



50.5"

14"

17"

## 3i-R Specifications

Description	Specification
Weight	93 lbs (42 kgs)
Dimensions	14" W x 17" D x 50.5" H (355.6mm W x 431.8mm D x 1270mm H)
Cold Tank Capacity	3 gallons (11 Liters)
Hot Tank Capacity	0.5 gallons (1.8 Liters)
Dispense Area	10.1" H (256mm H)
Reverse Osmosis Membrane Capacity	80 gallons per day
Reccomended Water Pressure	Do not exceed 60 psi
Rated Voltage/ Frequency	120v/60hz   220v/50hz
Power Consumption	Hot: 4.0A/410W   Cold: 1.5A/110W

## The Pure Water Technology Filtration Process




Unfiltered  
Water



Sediment  
Filter

Reduces Sediment  
• Dirt  
• Rust  
• Silt



Carbon Block  
Filter

Reduces Organics  
• Chemicals  
• Solvents  
• Chlorine



Reverse Osmosis  
Membrane

Reduces Inorganics  
• Lead  
• Mercury  
• Arsenic



Granular Activated  
Carbon Filter

"Polishes" Water  
For Great Taste



Boost  
Filter\*

Adds Alkalinity  
And Minerals



Ozone  
Injection

Helps Inhibit Growth Of:  
• Bacteria  
• Viruses  
• Parasites

\*Optional feature